

# TREX

BY TRECO



MUSICALLY AWESOME



# TREX ENIGMA SERIES TOWER SPEAKERS

Driver Enclosure Type : Bass Reflex • Driver Complement : 1" (2.54 cm) d (Round) Silk Dome, Wave Guide - Tweeter - 6.5" (16.51 cm) d (Round) - Bass Radiator - 4" (16.51 cm) d (Round) Dynamic Balance - Mid/Woofer

- Total Frequency Response : 30 Hz → 24,000 Hz • Nominal Impedance Range • 8 ohms → 4 ohms •
- Sensitivity (1 watt @ 1 meter), 90 dB Lower and Upper -3dB Limits 40 Hz → 30,000 Hz • RMS Power : 75 Watts
- Peak Power Handling : 150 watts • Height: 36.5" (92.71 cm) Width : 9.25" (23.5 cm) • Depth : 8.75" (22.23 cm) • Weight (Piece) : 13.50 Kg.

# TREX ARIA CENTER SPEAKER



Technical features : Decoupled Carbon Dome tweeter Solid Body Tweeter Description: 3-way vented-box system Drive units : 1x ø25mm (1 in) Decoupled Carbon Dome high-frequency - 1x ø25mm (4 in) : Air Motion Transformer Tweeter 4 Ohm high-frequency • 2x ø (8 in) midrange Frequency range : 45Hz and 33kHz • Frequency response - 50Hz - 28kHz ± 3dB Sensitivity 89dB spl (2.83Vrms, 1m)

- Harmonic distortion : 2nd and 3rd harmonics (90dB, 1m on axis) <0.5% 120Hz - 20kHz
- Nominal impedance : 8Ω (minimum 3.1Ω) • Recommended amplifier power : 30W - 200W into 8Ω on unclipped programme Dimensions • Height: (13.5in) cabinet including tweeter • Width : 628 mm (36 in) cabinet only • Depth : 318 mm (14.5 in) cabinet only including grille and terminals • Net weight 23kg.

# TREX INFINITY CINEMA SERIES (TRANSMISSION LINE)

Frequency Range : 30Hz-50kHz (-6dB) • Typical In-Room Bass response : 26Hz (-6dB) • Frequency Response: 46Hz-28kHz (±3dB): Harmonic Distortion: <0.3% 120Hz-20kHz (90dB, 1m) Maximum Output : 113dB • Amplifier Power : 100-500W (recommended) • Nominal Impedance : 8 Ohms (min.3.2Ohms) • Drive Units: Uni-Q Driver Array • HF: Air Motion Transformer Tweeter 4 Ohm MF: 2X 125mm (5in.) aluminium cone • Bass Driver - LF: 2x (8in.) hybrid aluminium Crossover Frequencies : 400Hz, 2.9kHz • Weight : 120.





# TREX<sup>SHANGRI LA</sup> CINEMA SERIES

Tweeter 3" SILK dome • Woofer (2) 4" bi-laminate paper

Bass Radiators (2) 10" passive radiators • Crossover Frequency 2700Hz

Recommended Amplification (wpc) 20–200W • Impedance Compatible with 4- and 8-ohm outputs

Overall Frequency Response 30Hz–40kHz • Sensitivity 91Db • Weight 17.00kg (p-XT70)

# TREX<sup>PRANAVA</sup> SURROUND SPEAKERS PAIR

Speaker Design 3-Way • Speaker Type Acoustic Suspension • Power Rating 70 140W Impedance 8 ohms • Frequency Response 40Hz - 23KHz • Sensitivity 90dB @2.80V/1 meter Crossover 2.5KHz  
• Shielded Yes Drivers : Tweeter 7/8" (2.2 cm) Dome Midrange 4.0" (10 cm) Woofer 8.0" (20 cm)  
• General : Dimensions (WxHxD) 12.5 x 16.2 x 13.2 • Weight 13.2 lbs (6.0)



# TREX<sup>NIRVANA</sup> CINEMA SERIES

Specifications : 2 x 8" Polycellulose Low-Frequency • Woofer : New High Definition Imaging (HDI) Waveguide : 2" (50mm) Aluminum Dome Tweeter : Yes • Recommended Amplifier Power: 20 – 225W Frequency Response: 30Hz – 40kHz • Sensitivity : 91dB @ 1M, 2.80V • Nominal Impedance: 6-8 Ohms Crossover Frequencies: 1.4kHz, 2.0kHz • Enclosure Type : Bass-Reflex via Rear-Firing Tuned Port Dimensions (W x D x H): 260 x 370 x 1070 (mm) • Weight : 25kg (49.74 lbs).





**TRECO TECHNOLOGIES PVT. LTD.**

Add.: A-7, 2nd Floor, Kailash Plaza,  
Acharya Niketan, Mayur Vihar-1,  
New Delhi-110091

(M): +91-98108 94981/ +91-99992 21655

(O): +91-11-45662460

Email id: [info@treco.in](mailto:info@treco.in) • Web: [www.treco.in](http://www.treco.in)

